

**Power cable (USB-C to USB-C) rc 1.5m white/silver E-mark IC, 100W 20V 5A/480Mbps**

|                       |  |
|-----------------------|--|
| Operating Temperature | 0 ÷ 45[°C]<br>1.5 m / 22#(65/0.08TC+500D)*2C+30#                                       |
| Length / cable type   | (11/0.08TC+250D)*4C+AL PVC Middle quilt<br>knitted with 24 spindles plus chanting yarn |
| Maximum Load          | 100W   |
| USB standard          | USB2.0   |
| Fast charge           | PD/QC  |
| Communication         | 30AWG/4C&22AWG/2C  |
| Transmission speed    | 480Mbps  |
| Weight                | N.W.: 37g / pc   |
| Packing bunch         | Various [pcs] 10   |



**Extension cable (USB-C to USB-C) rc 1.5m apple white**

|                       |   |
|-----------------------|---|
| Operating Temperature | 0 ÷ 45[°C]  |
| Length / cable type   | 1.5 m / 2464 20AWG/20+28AWG/3C White<br>PVC UL OD 4.5mm |
| Maximum Load          | 60W   |
| USB standard          | USB2.0  |
| Fast charge           | PD/QC   |
| Communication         | 26AWG   |
| Transmission speed    | 480Mbps   |
| Weight                | N.W.: 57g / pc  |
| Packing bunch         | Various [pcs] 10  |



**Extension cable (USB-C to USB-C) rc 1.5m black**

|                       |   |
|-----------------------|---|
| Operating Temperature | 0 ÷ 45[°C]  |
| Length / cable type   | 1.5 m / 2464 20AWG/20+28AWG/3C Black<br>PVC UL OD 4.5mm |
| Maximum Load          | 60W   |
| USB standard          | USB2.0  |
| Fast charge           | PD/QC   |
| Communication         | 26AWG   |
| Transmission speed    | 480Mbps   |
| Weight                | N.W.: 57g / pc  |
| Packing bunch         | Various [pcs] 10  |



**Extension cable (USB-A to USB-C) rc 1.0m or 1.5m black**

|                       |   |
|-----------------------|---|
| Operating Temperature | 0 ÷ 45[°C]  |
| Length / cable type   | 1.5 m / OD 4.5/50 2464 20ANG/2C+28ANG/30<br>Black/IC inside |
| Maximum Load          | 60W   |
| USB standard          | USB2.0  |
| Fast charge           | QC  |
| Communication         | 26AWG   |
| Transmission speed    | 480Mbps   |
| Weight                | N.W.: 48g / pc  |
| Packing bunch         | Various [pcs] 10  |



**Extension cable (USB-A to micro USB) rc 1.4m**

|                       |                            |
|-----------------------|----------------------------|
| Operating Temperature | 0 ÷ 45[°C]                 |
| Length / cable type   | 1.4m / 20AWG – round cable |
| Maximum Load          | 60W                        |
| USB standard          | USB2.0                     |
| Fast charge           | N/A                        |
| Communication         | 26AWG                      |
| Transmission speed    | 480Mbps                    |
| Weight                | N.W.: 36g / pc             |
| Packing bunch         | Various [pcs] 10           |

**Extension cable (USB-A to mini USB) rc 1.4m black or 1.8m white**

|                       |                                    |
|-----------------------|------------------------------------|
| Operating Temperature | 0 ÷ 45[°C]                         |
| Length / cable type   | 1,4m or 1,8m / 20AWG – round cable |
| Maximum Load          | 60W                                |
| USB standard          | USB2.0                             |
| Fast charge           | N/A                                |
| Communication         | 26AWG                              |
| Transmission speed    | 480Mbps                            |
| Weight                | N.W.: 37g / pc                     |
| Packing bunch         | Various [pcs] 10                   |

