

**IEC320-C5 (EU)**

Country of Origin : China  
 Operating Temperature : 0 ÷ 40 [°C]  
 Length/cord : 1.8m / 3x0.75mm2  
 Approvals : VDE 

Application	For Class I. Appliances	
WEIGHT / PACKING	1pc	N.W.: 174g / pc
	Box	0.55 x 0.36 x 0.20 [m]
		100pcs / 1box
		G.W.: 19.0kg / box




**IEC320-C5 (UK)**

Country of Origin : China  
 Operating Temperature : 0 ÷ 40[°C]  
 Length/cord : 1.8m / 3x0.75mm2  
 Approvals : ASTA 

Application	For Class I. Appliances	
UK Plug	The British Standards 1363 plug (13A Plug) IS 401 and IS 411 (Ireland), MS 589 (Malaysia) and SS 145 (Singapore), and SASO 2203 (Saudi Arabia).	
Fuse	3A / 250V	
WEIGHT / PACKING	1pc	N.W.: 174g / pc
	Box	0.56 x 0.36 x 0.20 [m]
		90pcs / 1box
		G.W.: 19.7kg / box



**IEC320-C5 (UL)**

Country of Origin : China  
 Operating Temperature : 0 ÷ 40 [°C]  
 Length/cord : 1.8m / 3x0.75mm2  
 Approvals : UL 

Application	For Class I. Appliances	
UL Plug	American standard NEMA 5-15	
	Canadian standard CS22.2, n°42	
WEIGHT / PACKING	1pc	N.W.: 72g / pc
	Box	0.56 x 0.36 x 0.20 [m]
		100pcs / 1box
		G.W.: 16kg / box

