


Country of Origin : China
 Operating Temperature : 0~40 [°C]
 Efficiency level (ErP) : 

GREEN MODE **RoHS**


Features:

LAN Activity Indicator: Detects if LAN is connected to device


Remote Reset Capability: Supports Airmax Bullet, Rocket, Nano, Pico

APPLICATION: telecommunication apparatus only

Specification:

Model	PoE-1215-M3	PoE-2424-M3
Size (L*W*H)	85 x 43 x 30 [mm]	85 x 55 x 33 [mm]
Output Voltage:	15VDC @0.8A	24VDC @1.0A
Input Voltage:	90-260VAC @47-63Hz	90-260VAC @47-63Hz
Input Current:	0.3A @120VAC, 0.2A @230VAC	0.3A @120VAC, 0.2A @230VAC
Inrush Current:	<15A peak @120VAC, <30A peak	<15A peak @120VAC, <30A peak
Efficiency	78%	78%
Output Ripple	1% Max (150mV)	1% Max (240mV)
Short Circuit	The adapter shall not damage by short the DC output to ground	The adapter shall not damage by short the DC output to ground
Peak Load Current	Max. 1.1A (time <60sec)	Max 1.3A (time <60sec)
Hold-up Time	10mS at typical input voltage and full load	10mS at typical input voltage and full load
Turn-on Delay	3sec at typical input voltage and load current	3sec at typical input voltage and load current
Over Current	Auto recovery	Auto recovery
Over Voltage Protection	Typ. 16.5V, Max 19.5V	Typ. 27.6V, Max. 32V
Switching Frequency	200kHz	200kHz
Line Regulation	+/- 0.5%	+/- 0.5%
Load Regulation	+/- 1%	+/- 1%
Suitable AC cable	IEC320-C5 ("Mickey Mouse")	IEC320-C5 ("Mickey Mouse")
Data IN / PoE	RJ45 Shielded Socket	RJ45 Shielded Socket
80% Current Indicator	Power LED will change color	Power LED will change color
Surge Protection	Common Mode	Common Mode
Shunt Capacitance	<5pF data	<5pF data
Response Time	<1Sec	<1Sec
Temperature	Operating: (0 ~ 40)°C / Storage: (-20 ~ 85)°C	Operating: (0 ~ 40)°C / Storage: (-20 ~ 85)°C
Humidity	Operating: 5% ~ 90% non condensing	Operating: 5% ~ 90% non condensing
SAFETY	CE FC TUV/GS cULud	
CE	EMC 2014/30/EU	
	LVD 2014/35/EU EN 60950	
WEIGHT / 1pc	N.W.: 0,092kg / pc G.W.: 0,105kg / pc	N.W.: 0,135kg / pc G.W.: 0,148kg / pc
PACKING / Box	0.410(L) x 0.280(W) x 0.240(H) [m]	
	96 pcs / 1box	
	G.W.: 11kg/box	G.W.: 15.2kg/box

Mechanical case specification of PoE-1215-M3 :



Mechanical case specification of PoE-2424-M3 :

