


Country of Origin : China
 Operating Temperature : 0~40 [°C]
 Dimension : 115 x 36 x 30 [mm]
 Car adapter : DC-DC convertor
 Approvals / Marks : 



Features:

Car adapter for notebook can be used in cars only (12V cigarette plug).

The set of five universal connectors. Ready for use with most of notebook brands using right choice of the DC connector size (Fujitsu Siemens, HP, Dell, IBM, Acer, Asus, Toshiba, SONY, Compaq etc.).

Output current & output voltage protection.

Input range (9 ~ 16)VDC. Power ON – Green LED.

For I.T.E. use only + RoHS conform.

Specification:

	Model	Voltage DC [V]	Min. Load [A]	Max. Load [A]	Efficiency [%]	Max. Power [W]	Ripple & Noise [mV]p-p max.	Connector [mm]
	YJIB-9020-C12	20	0	4.5	88	90	<240	5.5x7.9x11
INPUT	Voltage	(9 ~ 16)VDC						
	Input Current	11Amps max at any input voltage rated, DC output rated load.						
	Line/Load regulation	±3%/±5%						
	DC cable & connector	0.22m + cigarette lighter						
	Power Efficiency	88%						
	Input Fuse	15A protected against power line surges and any abnormal conditions						
OUTPUT	DC cable & connector	10A BLACK Standard length of the cable 1.5M±10cm & upon specification or customer requirements.						
	Power ON Led	Yes (Green @ adapter)						
PROTECTION	Short Circuit	The power supply will be auto recovered when short circuit faults remove.						
	Over Current	The power supply will be auto recovered when over current faults remove.						
	Insulation Resistance	-						
ENVIRONMENT	Cooling	The adapter is convention cooled only.						
	Temperature	Operating: (0 ~ 40)°C / Storage: (-10 ~ 80)°C						
	Humidity	Operating: (5 ~ 90)% RH / Storage: (5 ~ 90)% RH non condensing 72hrs						
OTHERS	Case material	-						
SAFETY	CE							
CE	EMC	2014/30/EU						
	LVD	2014/35/EU						
WEIGHT	1pc	N.W.: 0.173kg / pc G.W.: 0.214kg/pc						
		0.33 x 0.35 x 0.38 [m]						
PACKING	Box	50pcs / 1box						
		G.W.: 11.5 kg / box						

Mechanical case specification:

