

Country of Origin : China
 Operating Temperature : 0~40 [°C]
 Dimension : 75 x 34 x 43 [mm]
 Efficiency level (ErP) : VI

Approvals / Marks :



Specifications


Model	Voltage DC [V]	Loading [A]	Max. Power [W]	Ripple / Noise [mV] p-p	Connector [mm]
SYS1308N-2412-special	12	0~2.00	24	200	2.1x5.5x11

Features:

Output connector: standard: 2.1 x 5.5 x 11mm or customer requirement | Regulated Output With Low Ripple Noise | Safety Agency Requirements and EM/EMS Certified
 Private Label Marking Available | Modified and Custom Design Available | 2 Years Warranty


OUTPUT		CE	
Turn delay	3000ms max 3S max on the condition that input volotage 230V, full load.	EMC	2014/30/EU
Hold up time	5ms min@AC nominal input@output full load	LVD	2014/35/EU EN 62368-1
Efficiency	>86.2% min. Eff= 0.071 x ln(Po/1W) - 0.0014 x Po/1W + 0.67 Directive EU 2019/1782	SAFETY	
Transient response (dv,tmax)	0.6V dv max At AC nominal input loading from 20%load to 80% load 10ms tmax Dynamic rise time 10 us max,duty 40ms max,Dynamic load step is slew rate of 0.5A/us	CE	
Burn in limit	Ambient temp: 35C+~3%; 80% load; input voltage 230V; 2 hours.	OTHERS	
Power consumption	0.1W max. At AC nominal input@output min load	Dielectric Strength (Hi-pot)	HI-POT B / IEC 320 2pin primary to secondary 4000Vdc 10mA 1min
INPUT		M.T.B.F	500,000 Calculated Hours at 25°C, by Telcordia SR -332
Voltage	(90~264)VAC	Cable Length	1830mm (6 feet) standard cable or as required
Frequency	(47 ~ 63)Hz	PLD (power line disturbance)	Line power surge Line voltage SAG-more info on request
Current	1A rms@AC low line input and DC output full load	Cooling method	Natural Convection Cooling
Inrush Surge Current (cold start)	60A max@power supply cold start, ambient temperature 25°C @100Vac/240Vac nominal AC input	Housing material	PC
leakage current	<0.25 mA @ 240VAC input	Temperature coefficient:	<±0.5%/°C
PROTECTION		ENVIRONMENT	
Over current/ Short protection	The power supply will self-protect any output to ground, And auto recovery when abnormal circuit faults remove. An output short circuit is defined as any output impedance of less than 0.1 ohms.	Temperature	Operating: 0~40°C / Storage: -20~-85%RH non condensing
Over Voltage	The power supply will not be auto recovered when faults remove 110%-150%. (Voltage limit)	Humidity	Operating: 8%~90%RH / Storage: 5%~95% RH non condensing
Input protection	2A/250V Fuse. F2 connected from MOV(Varistor) to remaining PS circuitry to protect PS from excessive current draw.	WEIGHT	
No Load protection	The power supply is provided with no load operation to prevent the power supply and system from damage.	NW: 105g/pc + plug	
Protection class	II	GW: 122g/pc + plug	
		PACKING	
		Box	80 pcs/1 box

Mechanical case specification:




Cable specification:

A) DC- output: STP-1#18AWG*2C (2.1*5.5*11)



B) AC-input :



1. CORD MATERIAL: H03VVH2-F 2*0.75mm². (UL APPROVAL).
2. OUT JACKET: PVC. COLOR: BLACK.
3. RoHS CABLE
4. Double Insulation